



MITSUBISHI
HEAVY INDUSTRIES

PRO



R32



SRKYYP-W

9K to 18K BTU

24K BTU



SRKYYM-W



R32

UP TO 21.5 SEER

KEY FEATURES

Energy Savings • Jet Flow • Compact
for Space Saving • Self Diagnostic •
Quiet Operation



Distributed by:



Solutions

Indoor unit			SRK10YYP-W	SRK13YYP-W	SRK15YYP-W	
Outdoor unit			SRC10YYP-W	SRC13YYP-W	SRC15YYP-W	
Power source			1 Ph 220-240V 50 Hz / 220V 60Hz			
Cooling Capacity (Min-Max)		Btu/h	9,492 (3,412-10,236)	12,369 (3,412-12,966)	15,297 (4,436-16,378)	
SEER2			20	19	21	
Power Consumption	Cooling	kW	0.85	1.2	1.42	
		W	850	1200	1420	
COP	Cooling	W/W	3.29	3	3.17	
Max. Running Current		A	7.5	7.5	11.5	
Indoor Unit	Airflow Volume (Hi/Me/Lo/Ulo)	Cooling	CFM	240/159/98	335/247/105	339/254/105
	Sound pressure level (Hi/Me/Lo/Ulo)	Cooling	dB(A)	34/28/21	42/32/22	43/34/22
	Exterior dimensions (HxWxD)	Inch	10 1/2 x 30 5/6 x 8 1/4			
	Net weight	lb	17.63	17.63	17.63	
Outdoor Unit	Airflow Volume	Cooling	CFM	854	865	1017
	Sound pressure level	Cooling	dB(A)	47	50	52
	Exterior dimensions (HxWxD)	Inch	21 1/4 x 25 3/8 x 10 13/16	21 1/4 x 25 3/8 x 10 13/16	21 1/4 x 30 11/16 x 11 7/16	
	Net weight	lb	48.5	51.8	67.24	
Refrigerant	Type		R32	R32	R32	
	Factory Precharge	oz	14	18	26	
	Factory Charge Length	ft	30	30	50	
	Additional Charge	oz/ft	0.27	0.27	0.22	
Max Length		ft	50	50	80	
Piping size (Liquid/Gas)		Inch	(1/4) / (3/8)		(1/4) / (1/2)	
Vertical height differences	Outdoor is higher/lower	ft	MAX.33/MAX.33	MAX.33/MAX.33	MAX.49/MAX.49	

Indoor unit			SRK18YYP-W	SRK24YYM-W	
Outdoor unit			SRC18YYP-W	SRC24YYM-W	
Power source			1 Ph 220-240V 50 Hz / 220V 60Hz		
Cooling Capacity (Min-Max)		Btu/h	16,739 (3,412-18,084)	24,225 (3,753-25,931)	
SEER2			21.5	15	
Power Consumption	Cooling	kW	1.69	2.29	
		W	1690	2290	
COP	Cooling	W/W	2.96	3.1	
Max. Running Current		A	11.5	12.5	
Indoor Unit	Airflow Volume (Hi/Me/Lo/Ulo)	Cooling	CFM	346/282/116	607/529/370/222
	Sound pressure level (Hi/Me/Lo/Ulo)	Cooling	dB(A)	43/34/24	48/39/30/21
	Exterior dimensions (HxWxD)	Inch	11 4/7 x 39 2/7 x 9		
	Net weight	lb	17.63	25.35	
Outdoor Unit	Airflow Volume	Cooling	CFM	1123	1518
	Sound pressure level	Cooling	dB(A)	53	54
	Exterior dimensions (HxWxD)	Inch	21 1/4 x 30 11/16 x 11 7/16	25 3/16 x 31 1/2 x 11 7/16	
	Net weight	lb	67.24	84.87	
Refrigerant	Type		R32	R32	
	Factory Precharge	oz	26	20	
	Factory Charge Length	ft	50	50	
	Additional Charge	oz/ft	0.22	0.22	
Max Length		ft	80	65	
Piping size (Liquid/Gas)		Inch	(1/4) / (1/2)		
Vertical height differences	Outdoor is higher/lower	ft	MAX.49/MAX.49	MAX.65 / MAX.65	

Distributed by:



OF. CENTRAL 787-707-0556 CAPARRA 787-782-0282 BAYAMÓN 787-779-8233 RÍO PIEDRAS 787-281-7202 PONCE 787-842-2400 MAYAGÜEZ 787-834-1408

TOA BAJA 787-780-0390 CAGUAS 787-258-0708 ARECIBO 787-816-9079 HUMACAO 787-852-7772 DPTO. COMERCIAL 787-707-0556